



Product:	Super-Mat	Standard widths with borders:	85 cm, 115 cm and 150 cm
Customs tariff number:	57032098	Standard widths without borders:	3 cm smaller than for mats with borders (e.g. 82 cm)
Product details:	<ul style="list-style-type: none"> » Dual performance - scrape and wipe » Skid resistant rubber back » Light- and colour resistant » PVC-free » Suitable for underfloor heating » 5 years Manufacturers Guarantee* » 11 years warranty against significant colour loss » Made in Europe 	Standard lengths:	all lengths up to 400 cm
		Bespoke lengths:	up to 700 cm
		Colouration:	Solution dyed
Burning behaviour:	EN 13501-1 / Dfl-s1	Pile:	100 % High-Twist Nylon (HTN) Polyamide 6 with Monofilament
Static electrical propensity:	EN 14041 Antistatic	Pile height:	approx. 8 - 9 mm
Slip resistance:	NFSI High-Traction	Pile weight:	without substrate: 695 g/sqm with substrate: 940 g/sqm
Total mat weight:	3.10 kg/sqm	Backing:	100 % Nitrile rubber Available with kleeled or smooth backing
Overall height:	approx. 9 - 10 mm	Rubber thickness:	1.80 mm
Dirt absorption:	900 g/sqm	Rubber weight:	2.20 kg/sqm
Moisture absorption:	3 - 4 l/sqm	Border width:	20 mm
Application areas:	<ul style="list-style-type: none"> » Heavy traffic areas » Busy entrances 	Border thickness:	Available with or without borders 2.80 mm
		Cleaning:	Washable up to 60 °C » Tumble dry up to 60 °C

Colours:

